

# UNIKOTE FORM RELEASE

NEUTRAL PETROLEUM BASED FORM RELEASE AGENT

CONCRETE 3: FORM RELEASE AGENTS & TREATMENTS

## PRODUCT DESCRIPTION

A premium grade, chemically neutral, petroleum based form release agent. Unikote Form Release is non-reactive with the alkali in the concrete and creates a barrier that inhibits the bonding of fresh concrete to the formwork. Forms are ready for re-use almost instantly. Unikote Form Release produces a smooth, void free, architectural concrete surface. VOC compliant.

## GENERAL USES

Unikote Form Release will aid in the release of the form from hardened concrete on the widest range of forming material.

## FEATURES

- Ensures easy stripping of forms
- Produces smooth natural architectural surfaces – chemical action is not harmful to the concrete surface
- Will not retard, etch, or soften concrete surfaces, even if over-applied
- Run-down is reduced and reinforcing steel stays cleaner
- May be used on concrete structures that will store potable water
- Has a neutral release that keeps forms clean
- Repeated use makes wood forms water-repellent and extends their useful life
- Inhibits rust formation on steel forms
- Easy to apply
- No deleterious effect upon the natural bonding characteristics of secondary toppings or coatings, caulks, or sealants
- Reduces bug holes and extend the life of most forming materials
- Available in pine, cherry, orange, citrus fragrances  
(Indicate if fragrance is wanted when ordering)

## STANDARDS

Meets the requirements of Corps of Engineers specifications CW 03101, section 2.1.2.

VOC Compliant and Conforms to the Ozone Transportation Commission (OTC) guidelines for VOC regulations.

## INSTRUCTIONS FOR USE

Unikote Form Release should be applied in a thin uniform film with a sprayer, brush, or roller. No special application equipment is necessary, but a spray application is the most practical. Pounding or puddling is to be avoided.

Specific applications are as follows

### **Aluminum, High Density Plywood, Plastic, Steel:**

1750 sq. ft. per U.S. gallon

### **Medium Density Plywood:**

1500 sq. ft. per U.S. gallon

### **BB Grade Plyform:**

1000 sq. ft. per U.S. gallon

### **Plywood & other dimensional lumber:**

750 sq. ft. per U.S. gallon

## PACKAGING

- 275 gallon (1040.9 L) totes
- 55 gallon (208 L) drums
- 5 gallon (18.9 L) pails

## LIMITATIONS/WARNING

Do not over apply. Do not use as a bondbreaker for tilt-up construction.

Do not use on Styrofoam or latex molds. Do not use on plaster molds unless coated with a suitable sealer. Colder temperatures will increase the viscosity of Unikote Form Release.

### **Health Warning**

**Combustible...** Contains petroleum distillates. Keep out of reach of children. Do not take internally. Do not breathe vapors. Avoid prolonged contact with skin. If swallowed, call physician. If splashed in eyes, wash repeatedly with clean water and call physician. Keep away from heat, sparks and open flame. Refer to Material Safety Data Sheet before use.

**VOC content:** less than 250 g/L. Complies with USA and Federal AIM VOC standards. Do not thin or dilute.

## TECHNICAL SERVICES

Universal Building Products Inc. - Chemical Technical Service Department provides complete product and technical support.



**840 SOUTH 25TH AVENUE • BELLWOOD, ILLINOIS 60104 • 800 728 1958**

LIMITED WARRANTY NOTICE — Universal Building Products Inc. warrants that at the time and place we make shipment, our materials will be of good quality and will conform with our published specifications in force on the date of acceptance of the order. THE FOREGOING WARRANTY SHALL BE EXCLUSIVE AND IN LIEU OF ANY OTHER WARRANTY, EXPRESS OR IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE AND ALL OTHER WARRANTIES OTHERWISE ARISING BY OPERATION OF LAW, COURSE OF DEALING, CUSTOM OR TRADE OR OTHERWISE. As the exclusive remedy for breach of this Warranty, we will replace defective materials, provided, however, that the buyer examine the materials when received and promptly notify us in writing of any defect before the materials are used or incorporated into a structure. Twelve (12) months after Universal Building Products Inc. has shipped the materials, all our Warranty and other duties with respect to the quality of materials delivered shall conclusively be presumed to have been satisfied, all liability therefore terminates, and no action for breach of any duties may thereafter commence. Universal Building Products Inc. shall in no event be liable for consequential damages. Unless otherwise agreed to in writing, no warranty is made with respect to materials not manufactured for Universal Building Products. We cannot warrant or in any way guarantee any particular method of use of application or the performance of materials under any particular condition. Neither this Warranty nor our liability may be extended or amended by our salespeople, distributors or representative or by any sales information or drawings.

